



# NOVENCO product description

## Basic jet fans type AUT/ART-400



### Product

Basic jet fans in a unidirectional (AUT) and fully reversible (ART) version.  
The installation height is 422mm.

### Application

These compact and robust jet fans have been developed especially for the use in car parks.

The jet fans have been designed for an optimal capacity, long life span and very reliable operation.

### Construction

The jet fan consists of a round fan casing with an inlet cone on both sides to minimize the inlet losses.

The fan has been constructed with guide vanes for an optimal aerodynamic efficiency.

On both sides internal wire guards are mounted. With a special internal deflector the air stream flows in the desired direction.

On the reversible version internal deflectors are mounted on both sides of the fan.

As standard, the jet fans are equipped with mounting feet for direct mounting to the ceiling or wall.

### Novax impeller

The impeller consists of a Novax hub in which special aluminium impeller blades have been mounted at a pre-determined pitch angle.

The impeller is coupled directly onto the motor shaft.

All Novax fans are statically and dynamically balanced in accordance with VDI 2060, ISO 1940, 1-1986 Class Q 6.3.

### Motor

The motor is two-speed 3x400V, 50Hz or 3x380V, 60Hz for direct start. Motor protection min. IP55 in accordance with IEC 34-5. Insulation class F or H depending on temperature protection.

### Electric isolation

The jet fans have external terminal boxes.

### Surface treatment

As standard, all jet fans are delivered in a galvanized execution. A powder coating in any desired colour is available as an option.

In the standard execution the jet fans meet the requirements for operation in unheated, low corrosive environments according to DS/EN ISO 12944-2, corrosion category C3.

### Temperature resistance

The standard operating temperature is from -20 until +40°C..

Jet fans for hot smoke removal are certified according to the EN 12101 part 3 in the classes F200/F300/F400. Class F400 is only available for 50Hz.

The complete range of jet fans has been high temperature tested according to the table below:

Temp.	200°C	300°C	400°C
60min		X	
120min	X	X	X

High temperature test classes



# NOVENCO technical specification

## Basic jet fans type AUT/ART-400

Jet fan		AUT-400	ART-400
Execution	-	Unidirectional	100% reversible
Measured thrust	N	14 / 53	13 / 50
Sound pressure level*, re. $2 \times 10^{-5}$ Pa	dB(A)	54 / 72	56 / 75
Electrical connection	V, Hz	3x400V, 50Hz	3x380V, 60Hz

Motor details (standard temperature)					
Installed motor power	kW	0,3 / 1,1	0,3 / 1,1	0,3 / 1,3	0,3 / 1,3
Nominal current	A	0,8 / 2,7	0,9 / 2,7	0,9 / 3,1	1,0 / 3,2

Motor details (200°C)**					
Installed motor power	kW	0,3 / 1,1	0,3 / 1,1	0,3 / 1,3	0,3 / 1,3
Nominal current	A	0,6 / 2,5	0,7 / 2,7	0,7 / 2,9	0,8 / 3,2


Motor details (300°C)**					
Installed motor power	kW	0,3 / 1,1	0,3 / 1,1	0,3 / 1,3	0,3 / 1,3
Nominal current	A	0,6 / 2,5	0,7 / 2,7	0,7 / 2,9	0,8 / 3,2

Motor details (400°C)**					
Installed motor power	kW	0,3 / 1,1	-	0,3 / 1,3	-
Nominal current	A	0,6 / 2,5	-	0,7 / 2,9	-

Total weight	kg	63	63
--------------	----	----	----

\* Sound pressure level at 3m from the jet fans under the free field conditions at an angle of 45°

\*\* Complete jet fan is certified according EN 12101 part 3



Dimensions		A	B	C	D	E	ØR
AUT-400	mm	854	522	422	779	470	14
ART-400	mm	854	522	422	779	470	14

Data subject to change